
Printing date 21.03.2017

### Safety data sheet

according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017



	accordin	Safety data sheet g to 1907/2006/EC, Art	
Printing date 21.03.2	2017	Version number 3	Revision: 21.03.2017
Trade name: JOH	A Spirit varni	sh standard, coating	]
P403+P235 P501 • <b>Additional info</b> r 65.1 % of the mi	53 IF ON SKIN Rinse skin wi Store in a we Dispose of co international rmation: ixture consists o ckages where t	(or hair): Take off immed th water/shower. II-ventilated place. Keep co ontents/container in accord	dance with local/regional/national/
<ul> <li>Precautionary s</li> <li>P101 If medical</li> <li>P102 Keep out c</li> </ul>	ents aquatic life with statements advice is neede of reach of childr	n long lasting effects. d, have product container en.	or label at hand.
P103 Read labe • 2.3 Other hazar	ds		

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

Г

· Dangerous components.		
CAS: 64-17-5	ethanol	50-99%
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225	
CAS: 9005-90-7	Turpentine, venetian	2.5-<10%
EINECS: 232-688-5	<ul> <li>Aquatic Chronic 2, H411</li> <li>Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319</li> </ul>	
	<ul> <li>Turpentine, oil</li> <li>Flam. Liq. 3, H226</li> <li>Asp. Tox. 1, H304</li> <li>Aquatic Chronic 2, H411</li> <li>Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319</li> </ul>	0.25-<2.5%
Additional information: For the wording of the listed bazard phrases refer to section 16		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017

### Trade name: JOHA Spirit varnish standard, coating

- (Contd. of page 2) • After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special measures required.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017

### Trade name: JOHA Spirit varnish standard, coating

(Contd. of page 3)

	Is/personal protection		
· Additional information about design	• Additional information about design of technical facilities: No further data; see item 7.		
· 8.1 Control parameters			
<ul> <li>Ingredients with limit values that require monitoring at the workplace:</li> </ul>			
64-17-5 ethanol			
WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm			
8006-64-2 Turpentine, oil			
WEL Short-term value: 850 mg/m <sup>3</sup> , 150 ppm Long-term value: 566 mg/m <sup>3</sup> , 100 ppm			
• Additional information: The lists valid during the making were used as basis.			
<ul> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic me</li> </ul>	asures.		
Wash hands before breaks and at the	end of work.		
Respiratory protection: Not required.			
• Protection of hands: The glove material has to be imperme	eable and resistant to the product/ the substance/ th		
preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation			
			Material of gloves     The selection of the suitable gloves
further marks of quality and varies from preparation of several substances calculated in advance and has therefore. • Penetration time of glove material	om manufacturer to manufacturer. As the product is a , the resistance of the glove material can not be one to be checked prior to the application.		
further marks of quality and varies from preparation of several substances calculated in advance and has therefore. • <b>Penetration time of glove material</b> The exact break trough time has to gloves and has to be observed.	om manufacturer to manufacturer. As the product is a , the resistance of the glove material can not be one to be checked prior to the application.		
further marks of quality and varies from preparation of several substances calculated in advance and has therefore • <b>Penetration time of glove material</b> The exact break trough time has to gloves and has to be observed. • <b>Eye protection:</b>	be found out by the manufacturer of the protective		
further marks of quality and varies from preparation of several substances calculated in advance and has therefor • Penetration time of glove material The exact break trough time has to gloves and has to be observed. • Eye protection: Tightly sealed goggles SECTION 9: Physical and che • 9.1 Information on basic physical and • General Information • Appearance:	emical properties nd chemical properties		
further marks of quality and varies from preparation of several substances calculated in advance and has therefor • Penetration time of glove material The exact break trough time has to gloves and has to be observed. • Eye protection: Tightly sealed goggles SECTION 9: Physical and che • 9.1 Information on basic physical and • General Information	emical properties		
further marks of quality and varies from preparation of several substances calculated in advance and has therefore • Penetration time of glove material The exact break trough time has to gloves and has to be observed. • Eye protection: • Tightly sealed goggles • SECTION 9: Physical and chee • 9.1 Information on basic physical and • General Information • Appearance: Form: Colour: • Odour:	emical properties nd chemical properties Fluid Yellowish Alcohol-like		
further marks of quality and varies from preparation of several substances calculated in advance and has therefore • Penetration time of glove material The exact break trough time has to gloves and has to be observed. • Eye protection: Tightly sealed goggles • SECTION 9: Physical and chee • 9.1 Information on basic physical and • General Information • Appearance: Form: Colour:	emical properties nd chemical properties Fluid Fluid Yellowish		
further marks of quality and varies from preparation of several substances calculated in advance and has therefore • Penetration time of glove material The exact break trough time has to gloves and has to be observed. • Eye protection: • Tightly sealed goggles • SECTION 9: Physical and chee • 9.1 Information on basic physical and • General Information • Appearance: Form: Colour: • Odour:	emical properties nd chemical properties Fluid Yellowish Alcohol-like		
further marks of quality and varies from preparation of several substances calculated in advance and has therefor • Penetration time of glove material The exact break trough time has to gloves and has to be observed. • Eye protection: • Eye protection: • Tightly sealed goggles • SECTION 9: Physical and chee • 9.1 Information on basic physical and • General Information • Appearance: Form: Colour: • Odour: • Odour threshold:	emical properties Fluid Fluid Yellowish Alcohol-like Not determined.		





according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017

### Trade name: JOHA Spirit varnish standard, coating

	(Contd. of page 4)
Initial boiling point and boiling range	e: 78 °C
· Flash point:	13 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	3.5 Vol % 15.0 Vol %
<ul> <li>Vapour pressure at 20 °C:</li> </ul>	59 hPa
<ul> <li>Density:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	Not determined. Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> </ul>	Not determined. Not determined.
<ul> <li>Solvent content: Organic solvents:</li> </ul>	66.5 %
Solids content: · 9.2 Other information	33.6 % No further relevant information available.

### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- $\cdot$  11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017

### Printing date 21.03.2017 Trade name: JOHA Spirit varnish standard, coating (Contd. of page 5) · LD/LC50 values relevant for classification: 64-17-5 ethanol Oral LD50 3450 mg/kg (mouse) 7060 mg/kg (rat) 6300 mg/kg (rabbit) Dermal LD50 > 2000 mg/kg (rat) Inhalative LC50/4 h 20000 mg/l (rat) · Primary irritant effect: · Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Based on available data, the classification criteria are not met. · Respiratory or skin sensitisation Based on available data, the classification criteria are not met. · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. **SECTION 12: Ecological information** · 12.1 Toxicity · Aquatic toxicity: No further relevant information available. · Type of test Effective concentration Method Assessment 64-17-5 ethanol EC50 (48h) 9268 mg/l (daphnia magna) LC50 (48h) 8140 mg/l (gol) LC50 (24h) > 100 mg/l (daphnia magna) EC5 (16h) 6500 mg/l (Pseudomonas Putita) • 12.2 Persistence and degradability No further relevant information available. • 12.3 Bioaccumulative potential No further relevant information available. • 12.4 Mobility in soil No further relevant information available. · Ecotoxical effects: · Remark: Harmful to fish · Additional ecological information: · General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms · 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

GE

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017

### Trade name: JOHA Spirit varnish standard, coating

(Contd. of page 6)

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion
· 14.1 UN-Number · ADR, IMDG, IATA	UN1170
<ul> <li>· 14.2 UN proper shipping name</li> <li>· ADR</li> </ul>	1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
·IMDG	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
	ETHANOL SOLUTION
<ul> <li>· 14.3 Transport hazard class(es)</li> <li>· ADR, IMDG, IATA</li> </ul>	
· Class · Label	3 Flammable liquids. 3
<ul> <li>14.4 Packing group</li> <li>ADR, IMDG, IATA</li> </ul>	II
<ul> <li>· 14.5 Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>	No
• 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler): · EMS Number:	33 F-E,S-D
· Stowage Category	A
<ul> <li>14.7 Transport in bulk according to An II of Marpol and the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	1L Code: E2 Maximum net quantity per inner packaging 30 ml Maximum net quantity per outer packaging 500 ml
· Transport category	2
· Tunnel restriction code	D/E
	(Contd. on page 8



# Printing date 21.03.2017

### Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017

### Trade name: JOHA Spirit varnish standard, coating

	(Contd. of page 7)
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II

### **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements
- H225 Highly flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Version number 3

Revision: 21.03.2017

(Contd. of page 8)

GB

### Trade name: JOHA Spirit varnish standard, coating

#### · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# Relevant phrases H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: Abteilung Umweltschutz

· Contact: Hr. Hammerl

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 • \* Data compared to the previous version altered.