

Version number 6 (replaces version 5) Revision: 25.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: JOHA Spirit varnish la, primer, color varnish colorless, coating and guitar varnish
- · Article number:

1110 primer colorless, 1114 primer brown turbid,

1116 primer golden brown, 1650 Spirit varnish guitar varnish

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture For laquering a instrument.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hammerl GmbH & Co. KG

Geigenlacke / Violin varnishes

Hauptstraße 18

91083 Baiersdorf

Phone +49 (0)9133 2330

Fax +49 (0)9133 5171

e-mail joha@hammerl.com

· 1.4 Emergency telephone number:

Giftinformationszentrale Universitätsklinikum Mainz

International

24h Emergency number in German and English

Phone: +49 6131 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

(Contd. on page 2)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Spirit varnish Ia, primer, color varnish colorless, coating and guitar varnish

(Contd. of page 1)

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/

hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

73.5 % of the mixture consists of component(s) of unknown toxicity.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous compo | Dangerous components: | | |
|-------------------|---|--------|--|
| CAS: 64-17-5 | ethanol | 50-99% | |
| EINECS: 200-578-6 | ♦ Flam. Liq. 2, H225 | | |
| CAS: 78-93-3 | butanone | ≤2.5% | |
| EINECS: 201-159-0 | Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066 | | |

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)



Version number 6 (replaces version 5)

Trade name: JOHA Spirit varnish Ia, primer, color varnish colorless, coating and quitar varnish

(Contd. of page 2)

Revision: 25.02.2025

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

No special precautions are necessary if used correctly.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

(Contd. on page 4)



Version number 6 (replaces version 5)

Trade name: JOHA Spirit varnish la, primer, color varnish colorless, coating and quitar varnish

(Contd. of page 3)

Revision: 25.02.2025

Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state

Liquid

· Colour: According to product specification

· Odour:

Characteristic

· Odour threshold: Melting point/freezing point: Not determined. Undetermined.

· Boiling point or initial boiling point and

boiling range

78 °C

(Contd. on page 5)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Spirit varnish Ia, primer, color varnish colorless, coating and guitar varnish

(Contd. of page 4)

· Flammability Highly flammable.

Lower and upper explosion limit

Lower: 3.5 Vol %
Upper: 15 Vol %
Flash point: 13 °C
Auto-ignition temperature: 425 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 59 hPa

Density and/or relative density

Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.

9.2 Other information

· Appearance:

· Form: Fluid · Important information on protection of

health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: 73.9 % · Solids content: 25.0 %

· Change in condition

Evaporation rate Not determined.

· Information with regard to physical

hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Void
Void

(Contd. on page 6)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Spirit varnish Ia, primer, color varnish colorless, coating and guitar varnish

Contd. of page 5)

Corrosive to metals
Desensitised explosives

Void
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 values relevant for classification: | | | |
|---|-----------------|----------------------|--|
| 64-17-5 et | 64-17-5 ethanol | | |
| Oral | LD50 | 3,450 mg/kg (mouse) | |
| 7,060 mg/kg (rat) | | 7,060 mg/kg (rat) | |
| | | 6,300 mg/kg (rabbit) | |
| Dermal | LD50 | >2,000 mg/kg (rat) | |
| Inhalative | LC50/4 h | 20,000 mg/l (rat) | |

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

| · Endocri | ne disrupting properties | |
|-----------|--------------------------|---------|
| 78-93-3 | butanone | List II |

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 7)



Version number 6 (replaces version 5)

Trade name: JOHA Spirit varnish Ia, primer, color varnish colorless, coating and quitar varnish

(Contd. of page 6)

Revision: 25.02.2025

| · Type of tes | t Effective concentration Method Assessme | ent |
|---------------|---|-----|
| 64-17-5 eth | anol | |
| EC50 (48h) | 9,268 mg/l (daphnia magna) | |
| LC50 (48h) | 8,140 mg/l (gol) | |
| LC50 (24h) | >100 mg/l (daphnia magna) | |
| EC5 (16h) | 6,500 mg/l (Pseudomonas Putita) | |

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| · 14.1 UN number or ID number · ADR, IMDG, IATA | UN1170 |
|--|------------------------------|
| 14.2 UN proper shipping name | |
| · ADR | 1170 ETHANOL (ETHYL ALCOHOL) |
| · IMDG | ETHANOL (ETHYL ALCOHOL) |
| · IATA | ETHANOL ` |

(Contd. on page 8)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Spirit varnish Ia, primer, color varnish colorless, coating and quitar varnish

(Contd. of page 7)

| 14.3 Transport hazard class(es) | · 14.3 | Transpo | ort haza | ard cla | ss(es) |
|---|--------|---------|----------|---------|--------|
|---|--------|---------|----------|---------|--------|

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler

code): 33
• EMS Number: F-E,S-D
• Stowage Category A

14.7 Maritime transport in bulk according

to IMO instruments Not applicable.

Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)Code: E2

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

500 ml

· Transport category 2 · Tunnel restriction code D/E

· IMDC

Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

500 ml

· UN "Model Regulation": UN 1170 ETHANOL (ETHYL ALCOHOL), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 9)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Spirit varnish Ia, primer, color varnish colorless, coating and guitar varnish

(Contd. of page 8)

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/

hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Spirit varnish la, primer, color varnish colorless, coating and guitar varnish

(Contd. of page 9)

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Hr. Hammerl
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

GB