Revision: 25.02.2025



## Safety data sheet according to UK REACH

Version number 12 (replaces version 11)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish
- · Article number:

2210 primer, 2220 color varnish colorless, 2230 coating, 1660 guitar varnish

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture For laquering a instrument.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
   Hammerl GmbH & Co. KG

Geigenlacke / Violin varnishes Hauptstraße 18

91083 Baiersdorf

Phone +49 (0)9133 2330 Fax +49 (0)9133 5171

e-mail joha@hammerl.com

· 1.4 Emergency telephone number:

Giftinformationszentrale Universitätsklinikum Mainz

International

24h Emergency number in German and English

Phone: +49 6131 19240

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Carc. 1B H350 May cause cancer.



GHS07

Skin Sens. 1

H317 May cause an allergic skin reaction.

STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

(Contd. of page 1)



# Safety data sheet according to UK REACH

Printing date 10.03.2025 Version number 12 (replaces version 11)

Revision: 25.02.2025

Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

· Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

2-butanone oxime

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
EC number: 918-481-9	Kohlenwasserstoffe, C10-C13, n- Alkane, Isoalkane ringförmig <2% Aromagehalt  Asp. Tox. 1, H304	10-25%	
EC number: 919-857-5	Kohlenwasserstoffe, C9-C11, n-Alkane,Isoalkane, Cyclene, <2% Aromaten	≥10-<20%	
	<ul> <li>Flam. Liq. 3, H226</li> <li>Ox. Liq. 2, H272</li> <li>Asp. Tox. 1, H304</li> <li>STOT SE 3, H336</li> </ul>		
EC number: 920-134-1	Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cyclene <2% Aromaten	2.5-10%	
	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336		
		(Contd. on page 3)	

(Contd. on page 3)



Printing date 10.03.2025 Version number 12 (replaces version 11)

Revision: 25.02.2025

## Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	(Contd. of pa ≤2.5%
EINECS: 265-199-0	♦ Flam. Liq. 3, H226	
	♦ Asp. Tox. 1, H304	
	♦ STOT SE 3, H336	
CAS: 2457-01-4	Barumbis(2-ethylhexanoat)	≤2.5%
EINECS: 219-535-8	① Acute Tox. 4, H302; Acute Tox. 4, H332	
EC number: 905-562-9	reaction mass of ethylbenzene, m-xylene and p-xylene	≤2.5%
	<ul> <li>Flam. Liq. 3, H226</li> <li>STOT RE 2, H373; Asp. Tox. 1, H304</li> </ul>	
	Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 96-29-7	2-butanone oxime	≥0.1-<1%
EINECS: 202-496-6	Acute Tox. 3, H301	
	& Carc. 1B, H350; STOT SE 1, H370; STOT RE 2, H373	
	♠ Eye Dam. 1, H318	
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin	
	Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H336	
	ATE: LD50 oral: 100 mg/kg	
	LD50 dermal: 1,100 mg/kg	
CAS: 98-54-4 EINECS: 202-679-0	4-tert-butylphenol	≥0.025-<0.25
	Repr. 2, H361f	
	🄖 Eye Dam. 1, H318	
	Aquatic Chronic 1, H410	
	🔥 Skin Irrit. 2, H315	
CAS: 85203-81-2	2-Ethylhexansäure, Zinksalz, basisch	<2.5%
EINECS: 286-272-3	♣ Repr. 2, H361	
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	Aquatic Chronic 3, H412	

98-54-4 4-tert-butylphenol

Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB



5 Version number 12 (replaces version 11)

Revision: 25.02.2025

Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 3)

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Sand. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

GB

(Contd. on page 5)



Printing date 10.03.2025 Version number 12 (replaces version 11)

Revision: 25.02.2025

Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 4)

### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

### **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state

Liquid

· Colour:

Not determined.

· Odour:

Turpentine-like

(Contd. on page 6)



Printing date 10.03.2025 Version number 12 (replaces version 11)

Revision: 25.02.2025

## Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 5)

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 162 °C Flammability Flammable.

Lower and upper explosion limit

Lower: 0.7 Vol %
Upper: 6.4 Vol %
Flash point: 24 °C
Auto-ignition temperature: 230 °C

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 0.86 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

9.2 Other information

· Appearance:

Form: Fluid Important information on protection of

health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

· Organic solvents: 2.5 % · Solids content: 34.3 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical

hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids Void
Self-reactive substances and mixtures Void
Pyrophoric liquids Void
Pyrophoric solids Void
Self-heating substances and mixtures Void

(Contd. on page 7)



Printing date 10.03.2025 Version number 12 (replaces version 11)

Revision: 25.02.2025

Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 6)

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives
 Void
 Void
 Void

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

### 64742-95-6 Solvent naphtha (petroleum), light arom.

 Oral
 LD50
 >6,800 mg/kg (rat)

 Dermal
 LD50
 >3,400 mg/kg (rab)

 Inhalative
 LC50/4 h
 >10.2 mg/l (rat)

- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Carcinogenicity May cause cancer.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

98-54-4 4-tert-butylphenol

List I

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 8)



Version number 12 (replaces version 11) Revision: 25.02.2025

## Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 7)

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

4.4.4.11NL	
14.1 UN number or ID number ADR, IMDG, IATA	UN1263
	0111203
14.2 UN proper shipping name	4000 PAINIT
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids.
14.4 Packing group	III
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
	Warning: Flammable liquids.
14.6 Special precautions for user	
Hazard identification number (Kemler	
Hazard identification number (Kemler code):	30
Hazard identification number (Kemler	30 F-E, <u>S-E</u> A

(Contd. on page 9)



Printing date 10.03.2025 Version number 12 (replaces version 11) Revision: 25.02.2025

Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 8)

Transport/Additional information.	Additional inform	ation:
-----------------------------------	-------------------	--------

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

1000 ml

Transport categoryTunnel restriction codeD/E

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E1

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

2-butanone oxime

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

(Contd. on page 10)



Printing date 10.03.2025 Version number 12 (replaces version 11)

Revision: 25.02.2025

## Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 9)

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Substances of very high concern (SVHC) according to UK REACH

98-54-4 4-tert-butylphenol

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H272 May intensify fire; oxidiser.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H350 May cause cancer.

(Contd. on page 11)



Printing date 10.03.2025 Version number 12 (replaces version 11)

Revision: 25.02.2025

### Trade name: JOHA oil varnish standard, primer, color varnish colorless, coating, guitar varnish

(Contd. of page 10)

H361 Suspected of damaging fertility or the unborn child.

H361f Suspected of damaging fertility.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Abteilung Umweltschutz
- Contact: Hr. Hammerl
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement

Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids - Category 3

Ox. Liq. 2: Oxidizing liquids – Category 2 Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 1B: Carcinogenicity – Category 1B Repr. 2: Reproductive toxicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.