


Version number 5 (replaces version 4)

Revision: 25.02.2025





Version number 5 (replaces version 4)

Revision: 25.02.2025

ade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating		
	(Contd. of page 1	
	ause drowsiness or dizziness.	
<ul> <li>Precaution</li> </ul>	ary statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	
P210	Keep away from heat, hot surfaces, sparks, open flames and othe ignition sources. No smoking.	
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P303+P361	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing Rinse skin with water [or shower].	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national international regulations.	
· Additional	information:	
	e mixture consists of component(s) of unknown toxicity.	
2.3 Other h		
	PBT and vPvB assessment	
DBT. Not of	anliachta	

• **PBT:** Not applicable.

· vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

• Dangerous compor	nents:	
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol Flam. Liq. 3, H226 STOT SE 3, H336	50-99%
CAS: 64-17-5 EINECS: 200-578-6	ethanol 🚸 Flam. Liq. 2, H225	10-25%
CAS: 8006-64-2 EINECS: 232-350-7	<ul> <li>Turpentine, oil</li> <li>Flam. Liq. 3, H226</li> <li>Asp. Tox. 1, H304</li> <li>Aquatic Chronic 2, H411</li> <li>Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317</li> </ul>	≥0.25-<1%
CAS: 78-93-3 EINECS: 201-159-0	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	≤2.5%
· Additional informat	ion: For the wording of the listed hazard phrases refer to s	ection 16.

#### **SECTION 4: First aid measures**

#### • 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Immediately rinse with water.

- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

I. on page 3)



Version number 5 (replaces version 4)

Revision: 25.02.2025

(Contd. of page 2)

Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## **SECTION 6: Accidental release measures**

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

- Ensure adequate ventilation.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



ſ

# Safety data sheet according to UK REACH

Version number 5 (replaces version 4)

Revision: 25.02.2025

# Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating

(Contd. of page 3)

	8.1 Control parameters Ingredients with limit values that require monitoring at the workplace:				
107-9	8-2 1-methoxy-2-propanol				
	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm Sk				
64-17	/-5 ethanol				
WEL	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm				
8006	64-2 Turpentine, oil				
WEL	Short-term value: 850 mg/m³, 150 ppm Long-term value: 566 mg/m³, 100 ppm				
78-93	-3 butanone				
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV				
Ingre	dients with biological limit values:				
78-93	3-3 butanone				
	<ul> <li>V 70 μmol/L</li> <li>Medium: urine</li> <li>Sampling time: post shift</li> <li>Parameter: butan-2-one</li> <li>tional information: The lists valid during the making were used as basis.</li> </ul>				
	opriate engineering controls No further data; see section 7.				
Gene Imme Wash Resp In cas Ionge	idual protection measures, such as personal protective equipment eral protective and hygienic measures: ediately remove all soiled and contaminated clothing in hands before breaks and at the end of work. iratory protection: se of brief exposure or low pollution use respiratory filter device. In case of intensive r exposure use self-contained respiratory protective device.				
Gene Imme Wash Resp In cas Ionge	idual protection measures, such as personal protective equipment eral protective and hygienic measures: ediately remove all soiled and contaminated clothing in hands before breaks and at the end of work. iratory protection: se of brief exposure or low pollution use respiratory filter device. In case of intensive r exposure use self-contained respiratory protective device.				
Gene Imme Wash Resp In cas longe Hance The g prepa Due f the p Selec	idual protection measures, such as personal protective equipment eral protective and hygienic measures: ediately remove all soiled and contaminated clothing in hands before breaks and at the end of work. iratory protection: se of brief exposure or low pollution use respiratory filter device. In case of intensive r exposure use self-contained respiratory protective device. I protection				



Version number 5 (replaces version 4)

Revision: 25.02.2025

# Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating

(Contd. of page 4)

· Penetration time of glove material

SECTION OF Devotors and an

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

# · Eye/face protection



Tightly sealed goggles

9.1 Information on basic physical and General Information	
Physical state	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point an	
boiling range	78 °C
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	2.3 Vol %
Upper:	20 Vol %
Flash point:	32 °C
Auto-ignition temperature:	270 °C (DIN 51794)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (le	
value)	Not determined.
Vapour pressure at 20 °C:	59 hPa
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance: Form:	Fluid
Important information on protection	
health and environment, and on safety	
Ignition temperature: Explosive properties:	Product is not selfigniting. Product is not explosive. However, formation
Explosive properties:	explosive air/vapour mixtures are possible.
Solvent content:	explosive all/vapour mixtures are possible.
Organic solvents:	76.5 %
CHIMANIC SOLVANTS.	/0.0 70



Version number 5 (replaces version 4)

Revision: 25.02.2025

#### Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating (Contd. of page 5) · Solids content: 22.4 % · Change in condition Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void Flammable liquids Flammable liquid and vapour. · Flammable solids Void Self-reactive substances and mixtures Void Void · Pyrophoric liquids · Pyrophoric solids Void Self-heating substances and mixtures Void - Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void · Organic peroxides Void Corrosive to metals Void

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

Desensitised explosives

- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

Void

### **SECTION 11: Toxicological information**

- $^{\cdot}$  11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD50 LD50	<b>y-2-propanol</b> 4,016 mg/kg (rat) 13,000 mg/kg (rabbit)	
LD50	13 000 ma/ka (rabbit)	
	13,000 mg/kg (labbil)	
hanol		
LD50	3,450 mg/kg (mouse)	
	7,060 mg/kg (rat)	
	6,300 mg/kg (rabbit)	
		(Contd. on page
		D50 3,450 mg/kg (mouse) 7,060 mg/kg (rat)



Revision: 25.02.2025

(Contd. of page 6)

List II

# Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating

Dermal LD50 >2,000 mg/kg (rat)

Inhalative LC50/4 h 20,000 mg/l (rat)

· STOT-single exposure May cause drowsiness or dizziness.

11.2 Information on other hazards

#### Endocrine disrupting properties

78-93-3 butanone

### **SECTION 12: Ecological information**

#### · 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

• Type of test Effective concentration Method Assessment

107-98-2 1-methoxy-2-propanol

LC50 (48h) 23,300 mg/l (daphnia magna)

LC50 (96h) >6,800 mg/l (gol)

EC50 (3h) >1,000 mg/l (Pseudomonas Putita)

#### 64-17-5 ethanol

EC50 (48h) 9,268 mg/l (daphnia magna)

LC50 (48h) 8,140 mg/l (gol)

LC50 (24h) >100 mg/l (daphnia magna)

EC5 (16h) 6,500 mg/l (Pseudomonas Putita)

• **12.2 Persistence and degradability** No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

GP



Version number 5 (replaces version 4)

Revision: 25.02.2025

# Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating

(Contd. of page 7)

14.1 UN number or ID number ADR, IMDG, IATA	UN1170
14.2 UN proper shipping name ADR IMDG IATA	1170 ETHANOL (ETHYL ALCOHOL) ETHANOL (ETHYL ALCOHOL) ETHANOL
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler	Warning: Flammable liquids.
code): EMS Number: Stowage Category	30 F-E,S-D A
14.7 Maritime transport in bulk accordin to IMO instruments	<b>g</b> Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 3 ml Maximum net quantity per outer packaging 1000 ml
Transport category Tunnel restriction code	3 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 3 ml Maximum net quantity per outer packaging 1000 ml



Version number 5 (replaces version 4)

Revision: 25.02.2025

(Contd. of page 8)

# Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating

· UN "Model Regulation":

UN 1170 ETHANOL (ETHYL ALCOHOL), 3,

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

ш

· Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

#### Regulated poisons

None of the ingredients is listed.

#### Reportable explosives precursors

None of the ingredients is listed.

#### Reportable poisons

None of the ingredients is listed.

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. Hazard pictograms



· Signal word Warning

#### · Hazard-determining components of labelling:

1-methoxy-2-propanol

#### · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

#### Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- Read carefully and follow all instructions. P103
- Keep away from heat, hot surfaces, sparks, open flames and other P210 ignition sources. No smoking.
- Use explosion-proof [electrical/ventilating/lighting] equipment. P241

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.
- · Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 10)



Version number 5 (replaces version 4)

Revision: 25.02.2025

Trade name: JOHA Volatile oil varnish, primer, color varnish colorless, coating

(Contd. of page 9)

- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t • National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water. • 15.2 Chemical safety assessment:
- A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Hr. Hammerl

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Skin corrosion/irritation Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2 Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- Asp. Tox. 1: Aspiration hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2
- \*\* Data compared to the previous version altered.