Revision: 25.02.2025



## Safety data sheet according to UK REACH

Version number 6 (replaces version 5)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: JOHA Color extract golen yellow
- · Article number: 2902
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Dyestuff/Colouring agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  Hammerl GmbH & Co. KG
  Geigenlacke / Violin varnishes
  Hauptstraße 18
  91083 Baiersdorf
  Phone +49 (0)9133 2330
  Fax +49 (0)9133 5171
  e-mail joha@hammerl.com
- · 1.4 Emergency telephone number:

Giftinformationszentrale Universitätsklinikum Mainz International 24h Emergency number in German and English

Phone: +49 6131 19240

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

  The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms







GHS02 GHS07 GHS09

Signal word Warning

(Contd. on page 2)



Version number 6 (replaces version 5) Revision: 25.02.2025

### Trade name: JOHA Color extract golen yellow

(Contd. of page 1)

· Hazard-determining components of labelling:

1-methoxy-2-propanol

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains C.I. Solvent Yellow 82. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
CAS: 107-98-2	1-methoxy-2-propanol	50-99%	
EINECS: 203-539-1	<ul><li>Flam. Liq. 3, H226</li><li>STOT SE 3, H336</li></ul>		
CAS: 85029-59-0	Solvent Orange 54	2.5-10%	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410		
CAS: 85029-58-9	C.I. Solvent Yellow 82	≥0.25-<1%	
EINECS: 285-083-3	Aquatic Chronic 2, H411 Skin Sens. 1, H317		

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Color extract golen yellow

(Contd. of page 2)

**4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

.\_

(Contd. on page 4)



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Color extract golen yellow

(Contd. of page 3)

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

#### 107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

## **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state

Liquid

· Colour:

Orange

Odour:

Alcohol-like

(Contd. on page 5)



Version number 6 (replaces version 5) Revision: 25.02.2025

### Trade name: JOHA Color extract golen yellow

(Contd. of page 4)

· Odour threshold: Not determined.

· Melting point/freezing point: -96.7 °C

· Boiling point or initial boiling point and

boiling range 120 °C Flammability Flammable.

· Lower and upper explosion limit

Lower: 2.3 Vol %
Upper: ~20 Vol %
Flash point: 32 °C
Auto-ignition temperature: 270 °C

• **Decomposition temperature:** Not determined. PH Not determined.

· Viscosity:

Kinematic viscosity Dynamic: Not determined. Not determined.

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 12 hPa

· Density and/or relative density

Density at 20 °C: 0.962 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

Form: Fluid
 Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents:
Solids content:
Molecular weight
95.1 %
4.8 %
90.12 g/mol

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical

hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

(Contd. on page 6)



Version number 6 (replaces version 5) Revision: 25.02.2025

### Trade name: JOHA Color extract golen yellow

(Contd. of page 5)

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification	n
--	---

### 107-98-2 1-methoxy-2-propanol

Oral LD50 4,016 mg/kg (rat)
Dermal LD50 13,000 mg/kg (rabbit)

#### 85029-59-0 Solvent Orange 54

Oral LD50 >5,000 mg/kg (rat)

- · STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

<ul> <li>Type of test</li> </ul>	Effective concentration	Method	Assessment

### 107-98-2 1-methoxy-2-propanol

LC50 (48h) 23,300 mg/l (daphnia magna)

LC50 (96h) >6,800 mg/l (gol)

EC50 (3h) >1,000 mg/l (Pseudomonas Putita)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Version number 6 (replaces version 5) Revision: 25.02.2025

### Trade name: JOHA Color extract golen yellow

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN3092
· 14.2 UN proper shipping name · ADR · IMDG	3092 1-METHOXY-2-PROPANOL 1-METHOXY-2-PROPANOL, MARIN POLLUTANT
· IATA	1-METHOXY-2-PROPANOL
14.3 Transport hazard class(es)	
Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
14.5 Environmental hazards:	No
· Marine pollutant:	
· Marine poliutant:  · 14.6 Special precautions for user · Hazard identification number (Kemler code):	Warning: Flammable liquids.



Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Color extract golen yellow

	(Contd. of page 7		
· EMS Number: · Stowage Category	F-E,S-D A		
<u> </u>	14.7 Maritime transport in bulk according		
· Transport/Additional information:			
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/E		
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
· UN "Model Regulation":	UN 3092 1-METHOXY-2-PROPANOL, 3, III		

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

1-methoxy-2-propanol

(Contd. on page 9)



Version number 6 (replaces version 5) Revision: 25.02.2025

### Trade name: JOHA Color extract golen yellow

(Contd. of page 8)

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

## · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement

Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 10)

Page 10/10



## Safety data sheet according to UK REACH

Version number 6 (replaces version 5) Revision: 25.02.2025

Trade name: JOHA Color extract golen yellow

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.